

(i) a micro-flow reservoir system having at least one micro-flow reservoir including a reagent fluid comprising a sensing substance which reacts with the target chemical,

(ii) a sensor system comprising a thermopile for detecting the occurrence of said reaction connected to the micro-flow reservoir system,

(iii) a conduit connecting the micro-flow reservoir system and the sensor system for conveying reagent fluid in the micro-flow reservoir system to the sensor system,

immersing the sensing system in the test fluid, conveying the reagent fluid in the micro-flow system to the sensor system, and

detecting the occurrence of a reaction between the reagent fluid and the target chemical.

2. (Amended) A method according to claim 1 wherein the sensor system includes:

a thin film thermopile sensor having a plurality of sensing junctions and a plurality of reference junctions;

a hollow membrane fiber disposed proximate to each of said sensing junctions, wherein one end of said hollow membrane fiber is connected to the conduit means for receiving fluid from the micro-reservoir system and the other end is connected to a waste reservoir, said hollow membrane fiber having a porosity permitting passage therethrough of the target chemical from said test fluid while preventing passage therethrough of said sensing substance from said reagent fluid.

3. (Amended) A method according to claim 1 wherein said reagent fluid includes a catalyst.

4. (Amended) A method according to claim 3 wherein said catalyst is an enzyme which reacts with the target chemical to provide a heat that is proportional to the concentration of said target chemical.

5. (Amended) A method according to claim 4 wherein said enzyme is selected from the group consisting of glucose oxidase, catalase, hexokinase, glucose dehydrogenase, cholesterol oxidase, lactase, urate oxidase, trypsin, apyrase, penicillinase, and mixture thereof.

6. (Amended) A method according to claim 1 wherein said micro-flow reservoir system includes a micro-flow reservoir comprising a fluid including a calibration compound.

7. (Amended) A method according to claim 6 wherein said calibration compound is selected from the group consisting of hydrogen peroxide, catalase, glucose, target chemical, and mixtures thereof.

8. (Amended) A method according to claim 2 wherein said hollow membrane fiber comprises a semipermeable dialysis membrane, and wherein the outer diameter of said hollow membrane fiber is in thermal communication with said sensing junctions.

9. (Amended) A method according to claim 8 wherein said semipermeable dialysis membrane comprises a compound selected from the group consisting of acetate, polysulfone, polyacrylonitrile, cellulose, and mixtures thereof.

10. (Amended) A method according to claim 1 wherein said thermopile comprises:

OC17
a thin film thermopile disposed upon a supporting substrate, said thin film thermopile including a plurality of pairs of thin film thermocouple junctions, each of said pairs of thermocouple junctions including a reference junction and a sensing junction electrically coupled in series connection with one another and spaced apart from one another, said reference junction and a said sensing junction within each pair of thin film thermocouple junctions creating a temperature-dependent voltage when said reference junction and said sensing junction are electrically coupled in series connection, said plurality of pairs of thermocouple junctions being electrically coupled in series connection with one another between first and second output terminals, said plurality of pairs of thermocouple also having a plurality of output terminals which are individually attached to a subset of reference junctions along the thermopile length in between the first and second terminals; and

1
wiring means coupled to each of said output terminals of said plurality of pairs of thin film thermocouple junctions for providing a voltage difference signal proportional to a difference in temperature measured proximate the sensing and reference junctions arising from reactions between the reagent fluid and target chemical.

11. (Amended) A method according to claim 1 wherein the at least one reservoir including reagent fluid comprises:

a containment enclosing a collapsible bag that is held at positive pressure, said collapsible bag housing the reagent fluid; and

5217
a resistance tubing having an open end that is immersed in the reagent fluid to create sufficient fluidic resistance to control the flow rate of said reagent fluid through said open end of said resistance tubing.

5217
12. (Twice Amended) A method for determining the presence of a target chemical comprising:
providing a sensing system including:
(i) a micro-flow reservoir system having at least one micro-flow reservoir including a reagent fluid comprising a sensing substance which reacts with the target chemical,
(ii) a sensor system comprising an optical cell connected to the micro-flow reservoir system, and
(iii) a conduit connecting the micro-flow reservoir system and the sensor system,
immersing the sensing system in the test fluid,
conveying the reagent fluid in the micro-flow system to the sensor system, and
detecting the occurrence of a reaction between the reagent fluid and the target chemical.

5217
13. (Amended) A method according to claim 12 wherein the reagent fluid comprises a reagent which exhibits a measurable change in optical properties upon contacting the target chemical.

14. (Amended) A method according to claim 13 wherein said optical property is at least one selected from the group consisting of absorbance, fluorescence, color change, and chemiluminescence.

SC17
15. (Amended) A method according to claim 13 wherein said sensing arrangement further comprises a gas permeable membrane fiber which is connected between said conduit and said sensor such that said gas permeable membrane fiber is in fluid contact with the test fluid.

3
16. (Amended) A method according to claim 13 further comprising a micro-flow reservoir comprising a sweep fluid,

a conduit connecting said reservoir comprising a sweep fluid to one end of a hollow membrane fiber which is in fluid contact with said test fluid wherein the other end is connected to the conduit comprising the reagent fluid down flow from said sensor.

17. (Amended) A method according to claim 16 wherein the sweep fluid is selected from the group consisting of water and saline.

18. (Amended) A method according to claim 16 wherein said reagent is mixed with said sweep fluid, thereby causing a measurable optical change.

19. (Amended) A method according to claim 18 wherein said optical property is at least one selected from the group consisting of absorbance, fluorescence, color change, and chemiluminescence.